

U-PVC Profiles Vibrant Colours

Purple / Red / Pink / Orange / Green / Lime
/ Avocado / Blue / Grey / Black / White

A quality, cost efficient, high performance hygenic wall and ceiling systems that you can rely on. Our comprehensive cladding range offers a dependable, simple and attractive solution.

product information

Name:	U-PVC Profiles
Other names:	U-PVC Profiles
Abbreviation ISO 1043:	-

this document contains

» Technical Datasheet (Page 1)



U-PVC Profiles Vibrant Colours

Purple / Red / Pink / Orange / Green / Lime / Avocado / Blue / Grey / Black / White

technical properties

Physical Properties	Test	Unit	Result
1. Specific gravity	ISO 1183	kg/dm ³	1.530
2. Ash content	ISO 3451-5	%	16.5
Lower temp limit	ISO 182-2	min	46
Mechanical Properties	Test	Unit	Result
1. Yield stress	ISO 527-2	MPa	42
2. Elongation at break	ISO 527-2	%	120
3. Flexural E modulus	ISO 178	MPa	3350
Thermal Properties	Test Method	Unit	Result
1. Vicat-softening point	ISO 306	°C	74

All The above information is for guide purposes only. The data has been taken from standard test results provided by our manufacturers.

Key:

Yes	Limited	No or no data
+	o	-